



8Port Gigabyte POE

SP-PE1082-GB



Key Features

- 1-8 port POE 1GBps 9-10 Uplink 1GBps
- 200Mbps Full Duplex; 10 or 100Mbps Half Duplex
- Transmission up to 200 m
- Input Voltage 1A/220V AC
- Output Voltage: Each POE port +52V DC
- 120 W power Budget
- Protection: Overload/ Over Voltage/ Short Circuit

SP-PE1082-GB

Ports	:	PoE (1~8): 10/100/1000Mbps PoE ports (RJ45) Support btw 30W High Power, LAN (9~10): 10/100/1000Mbps uplink ports (RJ45)
Network Standard	:	IEEE 802.3i 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3x Flow Control, IEEE 802.3af/at/bt Power over Ethernet
Transmission Rate	:	200Mbps Full Duplex; 10 or 100Mbps Half Duplex
Transmission Distance	:	1~8 ports 250m 1000Mbps
Working Mode	:	Gigabyte (Default)
Network Latency	:	(100 to 1000Mbps): $\leq 16\mu s$ (use the 640byte package size)
Frame Filter & Transmission Rate	:	14800pps the most for 100Mbps port, 148800pps the most for 1000Mbps port
Power Budget	:	240W
Power Input	:	AC 90~240V, Total: $\leq 240W$
Power Output	:	PoE 1~8 Port: 1/2(+52V)
Watchdog	:	Port 1~8
Lightning Protection	:	6KV, Per: IEC61000-4-5
ESD Protection	:	8KV, Per: IEC61000-4-2
Operating Temperature	:	-30°C ~60°C
Operating Humidity	:	10%~90% (Non-condensing)
Storage Temperature	:	-40°C ~70°C
Storage Humidity	:	5%~90% (Non-condensing)
Dimension	:	12.8cm(L) x 19.4cm(W) x 4cm(H)
Weight	:	950g approx.