

IP 4MP Project Series

SP-IP4CVD-PA



Key Features

- High quality imaging with 5 MP, 2560 × 1440 resolution@20fps
- Smart Dual Light for Super Power Saving
- Up to 20 m white light distance for bright night imaging
- 3.6 mm fixed focal lens
- Plastic Body with Dust Resistant (IP66)
- 2D DNR

SP-IP4CVD-PA

| | | |
|--------------------------|---|--|
| Image sensor | : | 1/1.3" Sony Sensor |
| Signal system | : | Digital |
| Max. Resolution | : | 2560 (H) * 1440 (v) |
| Min. Illumination | : | 0.0003 Lux @ (F1.0, AGC ON), 0 Lux with white light |
| Light Alarm | : | Flashing Warm Light |
| Angle Adjustment | : | Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360° |
| Focal Length & FOV | : | 3.6 mm, horizontal FOV: 95°, vertical FOV: 50°, diagonal FOV: 115° |
| Max. Frame Rate | : | 1440p@20fps/3mp@20fps/1080p@25fps |
| Wide Dynamic Range (WDR) | : | ≥130 dB |
| White Light | : | Auto/Off |
| AGC | : | Yes |
| Day/Night Mode | : | Colour (Default)/BW |
| White Balance | : | Auto/Outdoor/Standard/Manual |
| Privacy Mask | : | 4 programmable privacy masks |
| Noise Reduction | : | 3D DNR/2D DNR |
| Image Settings | : | Anti-Banding; Smart Light; Brightness; Contrast; Mirror |
| White Light Range | : | up to 20 m |
| Material | : | Metal |
| Inbuilt Mic | : | YES |
| Weight | : | Approx. 515 g (1.14 lb.) |
| Protection | : | IP66 (Dome) |
| Power Supply | : | 12 VDC ± 25% |
| Consumption | : | Max. 5.3 W |